

Reflow Ovens – RK320 – RV380 - accessories and spare parts

Stand: 07.2025

Order no.	Designation	Description
Additional thermocouple with plug		
R1.1	Flexible thermocouple for internal connection	for RK320 / RK360 / RK460 - max temp. 350°C
Additional interfaces		
R2.1	Interface for external fume exhaust system	for RK320 / RK360 / RK460
	We need the technical data of your external fume exhaust system	
Nitrogen option		
R3.1	Automatic throttle valve incl. nitrogen connection	for RK320 / RK360 / RK460
External fume exhaust system		
R4.1	external fume exhaust system on request	different types possible
Spare parts		
R5.1	Assembled display panel for ProtoFlowS4	for RK320 / RK360 / RK460
R5.2	Configured Raspberry PI for ProtoFlowS4	for RK320 / RK360 / RK460
R5.3	Main controller board for ProtoFlowS4	for RK320
R5.4	Halogen heater: 230V / 800W / L=310 mm	for RK320
R5.5	Halogen heater: 230V / 500W / L=310 mm	for RK320
R5.6	Halogen heater: 230V / 800W / L=450 mm	for RK360 / RK460
R5.7	Halogen heater: 230V / 500W / L=450 mm	for RK360 / RK460
Support pins – Material PEEK		
R6.1	Support pin H=10 mm	for RK320 / RK360 / RK460
R6.2	Support pin H=15 mm	for RK320 / RK360 / RK460
R6.3	Support pin H=20 mm	for RK320 / RK360 / RK460
Grids		
R7.1	Grid – size ca. 298 x 275 mm	for RK320 / RK360 / RK460
R7.2	Grid – size ca. 440 x 360 mm	for RK360 / RK460
R7.3	Grid - other dimensions on request	for RK320 / RK360 / RK460